



## Ref. TAPALUZ

**Ancho/Width/Largeur:**  
290 cm

**Composición/Composition/Support:**  
100% Poliéster ignífugo FR  
100% Polyester Flame Retardant  
100% Polyester non feu

**Peso/Weight/Poids:**  
250 gr/m<sup>2</sup> (UNE EN 12.127)

**Resistencia a la abrasión/Abrasion  
resistance/Résistance à l'abrasion:**  
>20.000 Ciclos /Cycles /Cycles

**Resistencia a la tracción/ Breaking strenght /  
Résistance à le traction**  
TRAMA: 2.300 N URDIMBRE: 1.900 N (UNE EN ISO 13934-1)

**Calificación al fuego/Flameretardancy/  
Classement au Feu:**  
CLASE 1 (UNE EN 13773:2003)



**Solidez a la luz/Light fastness/  
Solidité lumière:**  
3-5 (UNE 105-B02-2001)

**Medidas de Absorción Acústica en laboratorio/  
Laboratory sound absorption measurements**

Coefficiente de absorción sonora ponderado/  
Weighted Sound Absorption Coefficient

$\alpha_w = 0,45$  (MH)

**Clase de absorción acústica / Acoustic class**  
D



► Las características técnicas especificadas en el presente documento tienen valor únicamente informativo careciendo de carácter vinculante. El fabricante se reserva el derecho de introducir modificaciones en cualquier momento por razones evolutivas de producto o de mercado. El color puede variar de una partida a otra.

► The technical characteristics specified in this document are strictly informative and not guaranteed. The manufacturer reserves the right to introduce modifications at its discretion at any time. Colour may vary from batch to another.

**Si necesita una muestra de color de 20 x 20 cm. por favor, solicítela a su proveedor habitual. Se la enviaremos al momento.**

**If you need any colour sample of 20 x 20 cm., do not hesitate in asking for it at his habitual supplier. We shall send it at once.**