

DABEDAN

TEJIDOS IGNÍFUGOS

RONDA 2

Ancho / Width / Largeur	300 cm
Composición / Composition / Support:	100% Polyester FR
Clasificació FR / Classment FR / FR Class:	C-1 (UNE EN 13773:2003), DIN 4102 B1(GER)*, M-1 NON FEU (FR)* CLASSE 1 (IT)*
Peso / Weight / Poids:	255 gr/m ² (+/- 5 %) (UNE EN 102.127)
Solidez a la luz / Light fastness / Solidité lumière:	4 - 5 (UNE 105-B02:1996)
Resistencia a la abrasión / Abrasion resistance / Résistance à l'abrasion	Matte face: > 65.000 c (UNE EN ISO12947-2:1999/AC:2006) Satin face: > 36.250 c (UNE EN ISO12947-2:1999/AC:2006)
Pilling	Matte face: Classe 2-3 (UNE EN ISO 12945-2:2001) Satin face: Clase 4-5 (UNE EN ISO 12945-2:2001)
Resistencia a la Tracción / Résistance à la Traction / Breaking Strength	Warp: 1.500 N Weft: 1.500 N (UNE EN ISO 13934-1:2013)
Resistencia a las costuras / Seam Strength / Résistance Couture	Warp: 1.00mm Weft: 1.30mm Category A (UNE EN 14465:2001+A1:2007)

*Further certificates upon demand



soft (C)



- Las características técnicas especificadas en el presente documento tienen valor únicamente informativo careciendo de carácter vinculante. El fabricante se reserva el derecho de introducir modificaciones en cualquier momento por razones evolutivas de producto o de mercado. El color puede variar de una partida a otra.

- *The technical characteristics specified in this document are strictly informative and not guaranteed. The manufacturer reserves the right to introduce modifications at its discretion at any time. Colour may vary from batch to another.*

Si necesita una muestra de color de 20 x 20 cm. por favor, solicítela a su proveedor habitual. Se la enviaremos al momento.

If you need any colour sample of 20 x 20 cm., do not hesitate in asking for it at his habitual supplier. We shall send it at once.